



Document Number V02_170117

Product specification

LSUM 016R2C 0500F EA AG



Product specification

■ Specification

1. Primary specification

Part number	Capacitance (F)	Max. ESR (mΩ)_DC	Max. Current (A) Non-repeated (Calculated value)	Leakage Current (mA)
LSUM 016R2C 0500F EA AG	500	1.7	2,100	< 5

2. Power & Energy

Part number	Usable Specific Power, P_d (W/kg) ¹	Impedance Match Specific Power, P_{max} (W/kg) ²	Energy Density (Wh/kg)	Max. Stored Energy (Wh)
LSUM 016R2C 0500F EA AG	3,100	6,500	3.1	18.2

3. Standard & Reliability

Rated Voltage	16.2 V		
Max. Voltage ³	17.1V		
Maximum series Voltage	750V		
Capacitance Tolerance	0% / +20%		
Operating temperature range	-40 ~ 65 °C		
Storage temperature range	-40 ~ 70 °C		
Max. continuous current ⁴	$\Delta T = 15$ °C	120A	
	$\Delta T = 40$ °C	200A	
Endurance Life (65°C)	1,500 Hours		
	Capacitance change	Within 20% of initially specified value	
	ESR change	Within 100% of initially specified value	
Projected Life Time (25°C)	10 Years at rated voltage		
	Capacitance change	Within 20% of initially specified value	
	ESR change	Within 100% of initially specified value	
Projected Cycle Life (25°C) ⁵	1,000,000 Cycles		
	Capacitance change	Within 20% of initially specified value	
	ESR change	Within 100% of initially specified value	
Shelf Life (25°C)	4 Years stored uncharged state		
Certifications	ROHS, REACH		

4. Monitoring

Part number	Temperature sensor	Temperature interface	Connector	Cell voltage monitoring	Balancing
LSUM 016R2C 0500F EA AG	NTC Thermistor	Analog	4 pin connector	Over Voltage Alarm (Optional)	Active or Passive

*Remarks

1) Usable specific power

$$P_d = \frac{0.12 \times V^2}{ESR \times mass}$$

2) Impedance match specific power

$$P_{max} = \frac{V^2}{4 \times ESR \times mass}$$

3) Non repeated, not to exceed 1sec.

4) Initial state value.

5) Actual cycle value can be subject to various application conditions.

Product specification

■ Safety & Physical Protection

Part number	Isolation voltage (DC)	Short circuit current(A)	Power Terminals	Recommended Torque - Terminal	Environmental Protection	Shock & vibration Protection
LSUM 016R2C 0500F EA AG	2.5kV	9,500	M8 / M10	20 / 30 Nm	TBD	TBD

Dimension in mm (not to scale)

■ Geometric properties

Part number	Dimension (mm)			Max. Weight (kg)
	Length	Width	Height	
LSUM 016R2C 0500F EA AG	470 ± 2	166 ± 1	70 ± 1	5.9

