



Document Number	V02_170117
-----------------	------------

Product specification

LSUM 0380R8L 0002F EA



Product specification

■ Specification

1. Primary specification

Part number	Capacitance (F)	Max. ESR (mΩ)_DC	Max. Current (A) Non-repeated (Calculated value)	Leakage Current (mA)
LSUM 0380R8L 0002F EA	2.5	650	180	< 12

2. Power & Energy

Part number	Usable Specific Power, P_d (W/kg) ¹	Impedance Match Specific Power, P_{max} (W/kg) ²	Energy Density (Wh/kg)	Max. Stored Energy (Wh)
LSUM 0380R8L 0002F EA	1,400	3,000	2.7	50.4

3. Standard & Reliability

Rated Voltage	380.8V		
Max. Voltage ³	408V		
Maximum Series Voltage	408V		
Capacitance Tolerance	0% / +20%		
Operating temperature range	-40 ~ 65 °C		
Storage temperature range	-40 ~ 70 °C		
Max. continuous current ⁴	$\Delta T = 15$ °C	7A	
	$\Delta T = 40$ °C	12A	
Endurance Life (65 °C)	1,500 Hours		
	Capacitance change	Within 20% of initially specified value	
	ESR change	Within 100% of initially specified value	
Projected Life Time (25 °C)	10 Years at rated voltage		
	Capacitance change	Within 20% of initially specified value	
	ESR change	Within 100% of initially specified value	
Projected Cycle Life (25 °C) ⁵	500,000 Cycles		
	Capacitance change	Within 20% of initially specified value	
	ESR change	Within 100% of initially specified value	
Shelf Life (25 °C)	4 Years stored uncharged state		

4. Monitoring

Part number	Temperature sensor	Temperature & Voltage interface	Connector	Cell voltage monitoring	Balancing
LSUM 0380R8L 0002F EA	PTC	Alarm	AMP178803-3	Over voltage alarm	Passive

*Remarks

1) Usable specific power

$$P_d = \frac{0.12 \times V^2}{ESR \times mass}$$

2) Impedance match specific power

$$P_{max} = \frac{V^2}{4 \times ESR \times mass}$$

3) Non repeated, not to exceed 1sec.

4) Initial state value.

5) Actual cycle value can be subject to various application conditions.

Product specification

Safety & Physical Protection

Part number	Isolation voltage (DC)	Short circuit current(A)	Power Terminals	Recommended Torque - Terminal	Shock & vibration Protection
LSUM 0380R8L 0002F EA	2.5KV	580	M6	6 Nm	IEC 60068-2-6

Dimension in mm (not to scale)

Geometric properties

Part number	Dimension (mm)			Weight (kg)
	Length	Width	Height	
LSUM 0380R8L 0002F EA	750±2	191±1	163±1	18.4±0.5

